

824 MHz to 960 MHz 14 dBi Aluminum Yagi Antenna, Black, N Type Female Connector



HG914YE-NF-BLK

Features

- 14 dBi gain & all weather Anodized Aluminum construction
- Can be installed for either vertical or horizontal polarization
- Heavy-duty 1/2" Aluminum boom
- 15 inch LMR®300 coax lead & all 1/8" thick plated steel mounting plate
- Solid Aluminum 1/8" elements
- Black powder coating to prevent weather deterioration

Applications

- 900 MHz ISM Band & Wireless LAN systems
- Point to Multipoint & Non Line of Sight (NLOS) Applications
- RFID & SCADA
- 900 MHz Cellular and GSM
- LPWAN, LoRA, IoT, M2M Applications

Description

The L-com HG914YE-NF-BLK High-Performance Yagi Antenna in an economical package combines accurate gain with a wide beam-width, ideally suited for directional applications in the 900MHz ISM and GSM bands. This series of Yagi antennas provides the user with an anodized aluminum boom, solid elements, low loss series LMR®300, and rugged mounting hardware.

This yagi antenna features 14 dBi of gain from 824 MHz to 960 MHz and an N Type Female connector. The L-com HG914YE-NF-BLK is powder coated with black paint to prevent icing or corrosion in harsh environmental conditions.

This 14 dBi 824 MHz to 960 MHz yagi antenna with a Female N Type connector, as well as our wide selection of superior quality RF parts, ships same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on antennas or other L-com products.

Configuration

Design	Portable
Band Type	Single
Polarization	Vertical/Horizontal
Cable Type	LMR300
Connector Type	N Female
Lightning Protection	DC Ground

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	824		960	MHz
Input VSWR			1.6:1	
Impedance		50		Ohms
Gain		14		dBi
Horizontal (Azimuth) HPBW		40		Degrees
Vertical (Elevation) HPBW		35		Degrees
Input Power			50	Watts

824 MHz to 960 MHz 14 dBi Aluminum Yagi
Antenna, Black, N Type Female Connector



HG914YE-NF-BLK

Mechanical Specifications

Size

Environmental Specifications

Temperature

Operating Range
Wind Survivability

-30 to +60 deg C
210 MPH [337.96 KPH]

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Radiation Pattern

Appendix

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

824 MHz to 960 MHz 14 dBi Aluminum Yagi Antenna, Black, N Type Female Connector from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

URL: <https://www.l-com.com/824-mhz-960-mhz-14-dbi-aluminum-yagi-antenna-black-n-type-female-connector-hg914ye-nf-blk.html>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.